

BEST A/V SYSTEMS CF ULTRA-SONIC COOL FOG HUMIDIFIER



- I Proportional or ON-OFF output**
- I Capacity: 0.3 ~ 30 LPH**
- I Fog Diameter $D_{32} = 2.92 \mu m$**
- I Instantly producing fog for fast humidification**
- I 304S.S. casing and inner tank: withstand corrosive media and weatherproof, suitable for clean rooms**
- I When equipped with Steam Dispersion Panel (option), Quick-Absorb or Final-Absorb, will be free of drip (water-drop / condensate)**
- I Low voltage: insure operation safety**
- I Adjustable output capacity of humidification & air-blow**
- I Water level sightglass, operation indicator, high/low water level indicator, and humidistat for easy inspection**
- I Flexible industrial pipe: durable, long-wearing, and easy to connect and fit all kinds of applications.**
- I The control box and fog generator can be combined as one unit or as two separate unit**
- I Built to order**

ULTRA-SONIC COOL FOG HUMIDIFIER CF-JS



- | TYPE (A): humidity auto control , display set and actual relative humidity.
- | TYPE (B): time control; operation on and off interval control.
- | Fog Diameter D_{32} : 1 ~ 10 μ m °
- | Quiet operation.
- | Low energy consumption, saving a lot of power bill.
- | Instant producing fog after power on; quick to humidifying and cooling down the temperature.
- | 304S.S. inner tank withstands corrosive media and with weatherproof coated casing.
- | Low voltage operation for safe operation.
- | Adjustable airflow output.
- | Linear humidity output or 100% capacity output or 80% capacity output.
- | Equipped with Supply water automatic control (solenoid valve control); low-water & overheat cutoff, fogging light, adding water light, short of water light, overheat light.
- | Control unit: humidity controller and sensor for Type A; timer for Type B.
- | 4-wheeled, quick and easy to move around.
- | Supply water: pressure at 1 ~ 4 kg/cm² clean pure water or softened and filtered city water.

MODEL	Capacity Kg/Hr	Airflow M ³ /Hr	Control Type	Power		App.Hum. Space M3	Dimension cm	Output Dia. mm	Wt. Kg
				VAC	W				
CF-JS03A/B	3	300	Auto and time set	110	450	120-200	45*29*40	75	23
CF-JS05A/B	5	350	Auto and time set	110	700	240-300	50*35*40	110	25
CF-JS10A/B	10	700	Auto and time set	220	1400	400-480	70*45*40	110*2	30

Ultra-Sonic Cool Fog Wind Direction Detector CF-WD



- I Portable wind direction detector.**
- I On-off control output.**
- I Capacity: 1.0 LPH**
- I Fog Diameter D_{32} : 1 ~ 5 μ m.**
- I Instant producing fog after power on.**
- I 304S.S. casing and inner tank: withstand corrosive media and weatherproof, suitable for clean rooms.**
- I Low voltage operation for safe operation.**
- I Adjustable airflow output.**
- I Water level window.**
- I Equipped with operation light, high water level light, and low water level listh.**
- I Flexible tube: durable and easy to connect with.**